AGRICULTURAL TRACTOR



MODEL: PAT900

TECHNICAL SPECIFICATIONS



MAIN SPECIFICATIONS

Type: 4x2

Traction force: (kN) 15.5

Max. power PTO shaft: (kW) 56.3 Wheelbase (front): (mm) 1400~1900 Wheelbase (rear): (mm) 1500~2100 Min. ground clearance: (mm) 450

Axle base: (mm) 2410 Turning radius: (m) 4.1±0.3

Weight: (kg) 3030



Model: DEUTZ WP4T90E23

Type: Direction injection, water-cooling, 4 strokes,

Rated Power: (HP) 90 Rated Speed: (rpm) 2300

No.of Cylinder: 4

TRANSMISSION

No. of Speed: 12F + 12R

CLUTCH

Clutch : LUK (Germany)

Type: Dry, Single, Dual Acting

CENTRAL DRIVE

Type: Spiral bevel gear

DIFFERENTIAL

Type: Closed, 4 planetary bevel gear

DIFFERENTIAL LOCK

Type: Lock pin type

TIRE

Size (Front/Rear): 7.50-20/14.90-30



BRAKE SYSTEM

Running brake: Hydrostatic, disk, wet Parking brake: Independent hand brake

STEERING SYSTEM

Type: Front wheel steering

Steering gear: Hydrostatic steering

HYDRAULIC SUSPENSION SYSTEM

Type: Split

Hydraulic system: Open-center

Setting pressure of safety valve: (MPa) 20.5-21.5

OPTIONAL

Cabin

Air Con

Disc Plow

Disc Harrow

Mower

Front Blade

4 in 1 Front Loader

Rear Backhoe

Sweeper

Trailer

Euro III Engine