MINI EXCAVATOR



MODEL: PP35E-IX

TECHNICAL SPECIFICATIONS



MAIN SPECIFICATIONS

Operating weight: (kg) 3080 Rated bucket capacity: (m³) 0.09

Overall length: (mm) 4510 Overall width: (mm) 1450 Overall height: (mm) 2395

Min. ground clearance: (mm) 292 Max. digging force: (kN) 17.4 Rotating Platform Speed: (rpm) 12

Gradeablility: (%) 60

WORKING RANGE

Max. digging radius: (mm) 4610

Max. digging height: (mm) 4205

Max. digging depth: (mm) 2610

Max. dumping height: (mm) 2840

Max. height digging radius: (mm) 2957

Max. dozing depth: (mm) 372

Max. dozing height: (mm) 262

Max. tail turning radius: (mm) 1346

ENGINE

Model: Kubota D1803 (Made in Japan)

Rated output: (HP) 31 Rated speed: (rpm) 2200

Emission: Euro III

UNDERCARRIAGE

Track length: (mm) 1935

Track ground length: (mm) 1454.5

Track gauge: (mm) 1934
Traction speed: (km/h) 2.4/4.3
Ground pressure: (kPa) 30

Track Roller: 2 Carrier Roller: 3

HYDRAULIC SYSTEM

Pump type: KYB

Hydraulic flow: (I/min) 76.3 Auxiliary flow: (I/min) 26.6



CABIN

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS air suspension driver's seat, streamline dashboard, air con and radio/mp3 player for extensive operations with well deserved comfort.

DOZER BLADE

Width: (mm) 1470 Height: (mm) 296

TRACTION SYSTEM

Track: Rubber / Steel

Track width RT (ST): (mm) 300

OPTIONAL ATTACHMENT

Quick Coupler Hydraulic Breaker