MOTOR GRADER



MODEL: PP120G-IX

TECHNICAL SPECIFICATIONS

POWERPLUS GROUPING, USA

MAIN SPECIFICATIONS

Operating Weight: (kg) 12500
Overall Length: (mm) 8060
Overall Height: (mm) 3370
Overall Width: (mm) 2600
Wheelbase: (mm) 5780
Tread: (mm) 2120

ENGINE

Model: CUMMINS 6BT5.9-C130 / POWERPLUS C125

Rated Power: (HP) 130 / 125 Rated Speed: (rpm) 2200

TRANSMISSION

YD13, Powershift, single-shift lever, neutral shift

lock device

Gear: 1 2 3 4 5 6 Forward:(km/h) 6.9 10.7 17.3 26.0 37.8 53.4

Reverse:(km/h) 6.9 17.3 37.8

DRIVE

Main Reducer: Spiral bevel gear, single stage Final Reducer: Single stage chain drive Tandem Drive: Double row roller chains

STEERING SYSTEM

Min. Turning Radius: (mm) 6600

Pivot Angle Frame: (°) 26

Max. Turning Angle (Front Wheel): (°) 49

AXLES

Ground Clearance: (mm) 430

Oscillating Angle: (°) 16

Rear: POWERPLUS (USA) Full Floating

Rear Tandem Axle

HYDRAULIC SYSTEM

Hydraulic Lock: MTC Technology (Italy)
Differential Lock: NO-SPIN (USA)

Oil Motor: EATON (USA)

Distributing Valve: HUSCO (USA)



BLADE EQUIPMENT

Blade Length x Height x Thickness:

(mm) 3658 x 545 x 16

Max. lifting height: (mm) 410 Max. grading depth: (mm) 560

Max. tilt angle: (°) 90 Rotating angle: (°) 360

Max. extending length(L/R): (mm) 2000

BRAKE SYSTEM

Service Brake: Full hydraulic & inner expanding

Parking Brake: Mechanical & inner-expanding brake type

TIRES

Size: 17.5 - 25 Ply Rating: 20

CABIN

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS air suspension driver's seat, streamline dashboard, air con and radio/mp3 player for extensive operations with well deserved comfort.

OPTIONAL

Scarifier

Ripper

Dozer

ROPS Cabin

MOBA (Germany) Averaging System