TRACTOR HEAD



MODEL: PT686Z-II

TECHNICAL SPECIFICATIONS



MAIN SPECIFICATIONS

Kerb Mass: (kg) 9400 GVM: (kg) 25000 GCW: (kg) 49000

Max. Speed: (km/h) 93 Min. turning circle: (m) 7.5

Min. ground clearance: (mm) 314

Max.gradeability: (%) 33

Overall Length: (mm) 7500

Overall Width: (mm) 2490

Overall Height: (mm) 3710

Wheel base: (mm) 3775+1400

Overhang (front): (mm) 1485

Overhang (rear): (mm) 725

Track width (front): (mm) 1860

Track width (rear): (mm) 1860

ENGINE

Model: STEYR WD12.375 Horsepower: (HP) 375 Emission: Euro II

Rated speed: (rpm) 2200

Max. Torque: (N.m/rpm) 1500/1100-1600

Type: In line, water-cooled, 6 cylinder,

pressure diesel engine

Cylinder Bore x Engine stroke: (mm) 126 x 155

TRANSMISSION

Model: FAST 9JS180

Gears: Forward 9 & Reverse 1

Gear Ratio: (F1)12.65 (F2)8.36 (F3)6.22 (F4)4.57

(F5)3.40 (F6)2.46 (F7)1.83 (F8)1.34

(F9)1.00 (R)13.22

CABIN

MAN-POWERPLUS cabin with air conditioner, CD player, flat head, double doors and tippable cabin. Designer upholstery.



STEERING UNIT

Type: ZF Technology, LHD / RHD

CLUTCH

GF430 Diaphragm Type

FUEL CAPACITY

Fuel Tank capacity: (L) 380

TIRES

No. of Tire: 10+1

Tire size: 12.00-20-18PR

Axle Drive: 6x6